

IN THE U.S. PATENT AND TRADEMARK OFFICE

2617

Appl. No.:

APPLICANTS: Ford et al.

SERIAL NO.: 10/725,274 FILING DATE: 11/25/2003

EXAMINER: Elcenko, Eric J ART UNIT:

ATTORNEY'S DOCKET NO.: 884A.0025.U1(US)

TITLE: DATA DELIVERY

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

DECLARATION UNDER 37 C.F.R. § 1.131

- 1. We, Peter J. Ford, Ian Nash, Ron Bird, Alan Wilkinson, Lee Cooper, Minna Asikainen, Inmaculada Espigares, Ari Tourunen, and Vesa-Matti Hakkarainen, hereby attest that we are the sole and first inventors of the invention described and claimed in the above-referenced patent application now pending before the U.S. Patent Office. Exhibits A through B described below represent our own work on the invention described in that patent application during the times indicated.
- 2. We conceived of the invention at least as early as September 11, 2003, as evidenced by Exhibit A.

Exhibit A in five (5) pages is an invention report that relates to that patent application and represents our own work on the invention while in the United Kingdom, Finland or in another World Trade Organization country.

Exhibit B is an email dated 11/09/2003 (September 11, 2003), the attachment in the email includes the document of Exhibit A.

While the invention report identifies Peter J. Ford, Ian Nash, Ron Bird, Alan Wilkinson, and Lee Cooper as the inventors, it is noted that the invention report describes improvements to the work of Minna Asikainen, Inmaculada Espigares, Ari Tourunen, and Vesa-Matti Hakkarainen who were subsequently identified as co-inventors.

3. We hereby attest that Exhibits A-B cited herein are true copies. We hereby acknowledge that the statements made herein are true or are made on information and belief that is believed to be true. We further acknowledge that any willful false statements are punishable by fine or imprisonment, or both, in accordance with 18 U.S.C. § 1001; and that such false statements may jeopardize the validity of any patent that may issue from the application to which this Declaration pertains.

Respectfully Submitted,

leto M	18 TH NOV 2000
Peter J. Ford	Date
lan Nash	Date
Ron Bird	Date
Alan Wilkinson	Date
Lee Cooper	Date
Minna Asikainen	Date
TOTAL AND	Date

Appl. No. 10/725,274 DECLARATION UNDER 37 C F R § 1 131

Minna Asikainen

Respectfully Submitted, Peter J. Ford Date Date 11/11/09 Ron Bird Date Alan Wilkinson Date Lee Cooper Date

Date

Respectfully Submitted,

•	
Peter J. Ford	Date
Ian Nash	
Tan Ivasii	Date
800	30.11.2009
Ron Bird	Date
Alan Wilkinson	Date
	·
Lee Cooper	Date
Minna Asikainen	Date
Minna Asikainen	Date

Appl. No. 10/725,274 DECLARATION UNDER 37 C.F R. § 1.131

Respectfully Submitted, Peter J. Ford Date Ian Nash Date Ron Bird Date Alan Wilkinson Date Lee Cooper Date Minna Asikainen Date

Appl. No. 10/725,274 DECLARATION UNDER 37 C.F.R. § 1.131

Respectfully Submitted, Peter J. Ford Date Ian Nash Date Ron Bird Date Alan Wilkinson Date Lee Cooper Minna Asikainen Date

Appl No 10/725,274 DECLARATION UNDER 37 C F R § 1.131

Respectfully Submitted,

Peter J. Ford	Date
Ian Nash	Date
Ron Bird	Date
Alan Wilkinson	Date
Lee Cooper	Date
Minna Asikainen	November 9, 2009

ApprilNo 16 705 274 DECLARATION UNDER 37 C.F.R. 6 1 131

Inmaculada Espigares	10 November 2009 Date
Ari Tourunen	Date
Vesa-Matti Hakkarainen	Date

Appl. No. 10/725,274 DECLARATION UNDER 37 C.F.R. § 1.131

Inmaculada Espigares	Date
Ari Tourunen	9.11.2009 Date
Vesa-Matti Hakkarainen	Date

^rAppl. No. 10/725,274 DECLARATION UNDER 37 C.F.R. § 1.131

Date		
Date		
3 NOVEMBER 2009 Date		



CONFIDENTIAL

EXHIBIT A

INVENTION REPORT

Title of the invention:		INVENTION REPORT RECEIVED			
Caller ID used to address new message		Code:	Patent Engineer/Committee:		
<u></u>	,,, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Place:	Date:		
Please type the description of the invention in this template. If you choose to use an attachment, make sure you answer all the questions in the template.		Signature of receiver:			
Names, employee numbers, job titles and nationalities of all inventors: Peter J Ford - Interaction design specialistIan Nash -Interaction design specialistRon Bird - Interaction design specialistAlan Wilkinson - Usability specialistLee Cooper - Usability specialist	Home addresinventors in r	sses of the respective order:	Business/Technology Units and cost centres: IBU - Caprice program - 3146726		
Email addresses of the inventors working outside the control of the first inventor acting as a		thwood, Building 1	, Desk 1505		
Phone of the first inventor: 7620		the first inventor:			
Line manager(s): Ruth Lyburn	1				
Project: Caprice	Proiect	Manager: Olli Hut	tunen		
Related product(s): Charlie			S functionality - See What I See		
The invention becomes public on (see section 1	E .		<u>-</u>		
I am/ We are the sole/ and original inventor(s) or	f this inventio	n.			
The company may, by virtue of applicable legisla I/ We acknowledge my/ our obligation to sign as the invention in different countries.	auon, de entit inventor(s) a	iea to tuii or partial Il documents that r	ngnis to the invention. nay be required for protecting		
Applicable to inventions made by inventors of Unless the inventor requests the Invention Report Invention Report is received or such other period otherwise require, the inventor consents to the revaluation of the invention. A reasonable period If I/We request that the Invention Report be re-	ort to be respo d as the mand ight of the em d of time may d	onded to within fou datory provisions o aployer to use a rea exceed four (4) mo	r (4) months from the date this If the applicable local law may asonable period of time for the onths.		
Date:					
I have read and understood the invention descri	bed in this In	vention Report			
Date: Signature of Manager or Patent Engineer					



CONFIDENTIAL

S	iar	atı	ireí	(s)	of	Ir	iven	tor	(e)	١
v			•• ••	•	~,					٠.

ار ولا غر د نگ

FORMAL REQUIREMENTS FOR FILING THE INVENTION REPORT

The invention report must have the names of all the inventors and their home addresses. The first mentioned inventor is assumed to be the contact person in matters concerning the invention report. In the fields of office address, phone and fax, please fill in the contact person's information. Fill in the project field, if the invention is made in a project. The original Invention Report is signed by all inventors. Each page of the original invention report is signed by a manager. In case it is difficult to obtain the manager's signature your patent department will take care of it. The signed invention report is given directly to the local or business or unit's patent department. The invention report should also be submitted electronically to the patent department of the business or technology unit.

I have read and understood the invention described in this Invention Report

Date:

Signature of Manager or Patent Engineer

NOKIA

CONFIDENTIAL

DESCRIPTION OF THE INVENTION

1. Field of technology and background

Describe here the technology and the areas of use the invention relates to. Provide here <u>general background</u> <u>knowledge that is required to understand</u> the framework of the invention, and describe the problem to be solved and the invention later.

The invention uses the caller ID (CLI) to look up contact details to allow automatic addressing of text, multimedia email or other to the person connected to the device via voice call

2. Problem

Describe here the problem that the invention solves or the situation that the invention improves, and preferably concentrate on the technical aspects of the problem or the situation.

Currently the user would have to address the message manually – taking time, and causing confusion in the interaction as to whether the call is still active or not

3. Prior art

Describe here <u>how the problem was solved earlier</u>. Please <u>state also the source of prior art accurately.</u>

Manual addressing of messages

4. Invention

Put here a short <u>crystallization of the invention</u> on a general level including possible use cases.

Use case: - User is in a phone conversation and is trying to describe something to the other person. Instead of wasting time, they decide to take a picture and send it to the caller in the line. They take the picture, and in the menu there is the option to 'send to caller'. This then looks up the callers contact list and returns the possible sending options based on the contact details – for an image this will be MMS or Email (unless there is no email address in which case it will aut0-select MMS)

The message is automatically addressed with the image attached in one hit – no long winded messaging interactions required.

5. Implementation

Describe exemplary <u>implementations in detail</u> with alternatives here, including at least the implementation you consider to be the best. <u>Describe the crucial</u> elements in detail.

CLI needs to be able to look up contacts list and parse for suitable messaging types.

Menu needs to offer the 'send to caller' option only when 'in call'

6. Advantages and disadvantages

Describe here <u>how the invention improves</u> earlier solutions. Also, if you are aware of any <u>advantages or disadvantages</u>, please state them here.

Advantages:

Fast sending of an image to a caller

Less confusion as no context switch to messaging is required

No manual addressing required

7. List of figures

Write the figure captions here as a list (Figure 1 presents ..., Figure 2 presents ...) and include the images into

I have read and understood the invention described in this Invention Report

Date:

Signature of Manager or Patent Engineer

NOKIA

CONFIDENTIAL

the invention report (section 5 or section 15) in Word-compatible format (i.e., no embedded images that won't show on the screen when the document is viewed) labelled with the figure number (Figure 1., Figure 2.). Alternatively, include the figures in a separate document (PowerPoint etc.), but make sure to include the description of the figures also here.

None

8. List of abbreviations

CLI - caller line identification

9. Supervision

Explain here how we can (if possible) recognise if a competitor is using the same product/feature.

Watch the imaging phone marketplace

10. Commercial value

Evaluate three aspects here: **a)** is the invention planned to be <u>used in a Nokia product</u> (which), **b)** is the invention going to be <u>proposed to a standard</u> (which), and **c)** would Nokia's <u>competitors benefit from the use</u> of the invention (who/how)?

- a) yes Caprice under the support for SWIS lite requirements
- b) it is based on the SWIS standard
- c) Imaging phone competitors would want to use this feature Samsung etc...

11. Publication

If the invention is becoming public in any way, please <u>describe the exact way and details of publication</u> here: what will be disclosed and how. For example, submission of standardization contributions, scientific papers, conference abstracts, theses or papers written for a degree and commercial brochures and offers for sale may be considered as "publication". Also, any use in a product that is publicly available or disclosure (written or oral) to another company without a non-disclosure agreement (NDA) is considered to be a publication.

Caprice Q1 2005

12. Dates of the invention

If you can, put here the date when you first thought of the invention (this date should be verifiable from your personal dated notes). Also, if you have completed the invention, e.g., written a computer program, put this date here (the completion should be verifiable by a witness). Also, provide all evidence material relating to the dates to the patent department.

13. Experts

If you know any <u>experts</u> that are able to comment the invention, list them here. Also, please mention if you are aware that a certain <u>patent engineer</u> has earlier experience of similar invention reports.

I have read and understood the invention described in this Invention Report

Date:

Signature of Manager or Patent Engineer

NOKIA

CONFIDENTIAL

14. Further comments

Any further comments may be put here, e.g., if you consider the invention to require further development, know of a related earlier invention report in Nokia by you or others, or have any additional information that you think may otherwise affect the decision process.

Caprice inherited this feature and so there may be prior art from with Nokia itself - this should be investigated as the Marketing name for this functions was on the intranet - Here: http://www2.connecting.nokia.com/nmp/ipc_intranet.nsf/document/ES335LE8X4?OpenDocument

15. The figures

Place the figures here, or among the description of the implementation. Alternatively, include the figures in a separate document (PowerPoint etd).

not publiculty avantable - chested 17/10/03 Parthyri

I have read and understood the invention described in this Invention Report

Patent-Agency Swindell-Pearson (EXT-RES/Southwood)

From: To:

Khan Saiful (Nokia-IPR/Southwood)

Patent-Agency Swindell-Pearson (EXT-RES/Southwood)

Cc:

Mallipeddi Vijaya (Nokia-IPR/Southwood)

Subject: New Draft NC33884

Attachments: NC33884.doc(1MB)

EXHIBIT B

Sent:Thu 11/09/2003 12:04

Paul,

I attach herewith an electronic copy of documents relating to NC33884. Please note that the document contains embedded files (please note that some of the embedded files appear as the front page of the document - you will need to double-click on this front page to get access to the whole embedded doc.).

Please prepare a draft patent application for my approval as soon as possible. I wish to have this case filed by November. Please first file this case in the US.

Thanks

Saiful

Dr Saiful Khan IPR Counsel NOKIA

Nokia IPR Department Nokia House Building 3, Floor 2 Summit Avenue Farnborough GU14 ONĞ UK

Tel: +44 (0) 1252 867597 Fax: +44 (0) 1252 865080 Email: saiful.khan@nokia.com

Notice of Confidentiality: This message is:

- (1) subject to the attorney-client privilege;
- (2) attorney work product; and/or
- (3) confidential information of NOKIA CORPORATION and all its subsidiaries

This message is intended only for the individual or entity to whom it is addressed. Any disclosure, copying, or distribution of the contents of this message outside of the intended recipients or employees of NOKIA CORPORATION or any of its subsidiaries, with a need to know such information, is prohibited.

Peter J Ford

Nash . Ron Bird

UI - images.

Patent-Agency Swindell-Pearson (EXT-RES/Southwood) From: Patent-Agency Swindell-Pearson (EXT-RES/Southwood) Sent:Wed 22/10/2003 15:08 Khan Saiful (Nokia-IPR/Southwood) To:

Cc:

Subject: NC33884us, 8579us, First Draft Patent Appln

Attachments: 8579us.pdf(879KB) 28579us.001.doc(56KB)

21st October 2003

EXHIBIT C

Dear Saiful.

NC 33884 - Draft Patent Application

Our File: PH/8579US

Please find enclosed a first draft patent application for this invention. You will see from the enclosed claims that I have identified two potentially inventive aspects of this invention. The first relates to the mechanism by which a data message can be automatically addressed during a telephone call. The second relates to a "context aware" menu, which provides an option "send to caller" only during a telephone call.

The first page of the draft, rather unusually, sets out the inventors for this invention. This is because this invention was separately innovated in separate parts of Nokia. I have the inventors' details for the U.K. inventors but not for the Finnish inventors. I would prefer to have details of the Finnish inventors before instructing the filing of the U.S. application.

I discussed this case with Peter Ford and Alan Wilkinson. Peter Ford will by now have left Nokia and Alan Wilkinson has agreed to be the primary contact for this case.

I look forward to receiving any comments you or the inventors may have concerning this draft.

https://xesife001.nokia.com/exchange/EXT-Swindell-Pearson.Patent-Agency/Sent%20Ite... 22/10/2003

Yours sincerely,

Paul Higgin

EXHIBIT D

1

Contact: Alan Wilkinson

Inventors:

5

Э			
	1. Peter J Ford	UK	Left Nokia
	2. lan Nash	UK	
	3. Ron Bird	UK	
	4. Alan Wilkinson	UK	
10	5. Lee Cooper	UK	
	6. Minna Asikainen	Tampere?	
	7. Inmaculada Espigares	Tampere?	
	8. Ari Tourunen	Tampere?	
	9. Vesa-Matti Hakkarainen	Tampere?	

15

Address and nationality details are required for inventors 6 to 9.

TITLE

30

Data delivery.

FIELD OF THE INVENTION

5 Embodiments of the present invention relate to methods and devices for sending data.

BACKGROUND TO THE INVENTION

At present, if a user wishes, for example, to send a text message, the user must enter a text messaging application, write the message and then specify the address to which it should be sent before sending the messaging.

It would be desirable to improve the ease with which a user can send data using a mobile telephone.

BRIEF DESCRIPTION OF THE INVENTION

The inventors realised that the process by which data is sent by a mobile cellular telephone can be improved when the telephone is participating in a telephone call.

The inventors realised that when a party to an on-going telephone call wishes to send data during the telephone call, they will often wish to send that data to the other party or parties participating in the on-going telephone call.

According to one embodiment there is provided a method of sending data from a first party participating in a telephone call to a second party participating in the telephone call, comprising, in the terminal of the first party, storing, as a consequence of the telephone call, identifier data that identifies the second party;

using the stored identifier data to determine automatically a destination address for a data message; and sending, during the telephone call, the data message with the automatically determined destination address.

- According to another embodiment there is provided a mobile cellular telephone terminal comprising: a radio cellular transceiver for enabling participation in a telephone call to a second terminal; a memory; and control means for storing in the memory, as a consequence of the telephone call, identifier data identifying the second terminal or its user, for determining automatically a destination address for a data message using the stored identifier data and for controlling the radio cellular transceiver to send the data message with the automatically determined destination address during the telephone call.
- 15 According to another embodiment there is provided a method for sending data from a first party participating in a telephone call to a second party participating in the telephone call, comprising, in the terminal of the first party: providing, while the telephone call is on-going, a user selectable option to transfer data to another party participating in the telephone call without user specification of a destination address.

According to another embodiment there is provided a mobile cellular telephone terminal comprising: a radio cellular transceiver for enabling participation in a telephone call to a second terminal; a user interface; and control means for providing, temporarily while the telephone call is on-going, in the user interface a user selectable option to transfer data to another party participating in the telephone call without user specification of a destination address.

25

30 Embodiments of the invention therefore provide an easier and faster way to send data to a likely recipient during a telephone call.

BRIEF DESCIPTION OF THE DRAWINGS

For a better understanding of the present invention reference will now be made by way of example only to the accompanying drawings in which:

- Fig. 1 illustrates a mobile cellular radio telecommunications network 2;
 Fig. 2 illustrates the first mobile cellular telephone terminal 6 in more detail;
 Fig 3 illustrates the process by which data is sent by the first terminal to the second terminal while it is participating in a telephone call with the second terminal; and
- Fig 4 illustrates an alternative process by which data is sent by the first terminal to the second terminal while it is participating in a telephone call with the second terminal.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

15

20

Fig. 1 illustrates a mobile cellular radio telecommunications network 2. The network 2 comprises network infrastructure 4 that typically includes a switching centre connected to a plurality of base transceiver stations, a first cellular mobile telephone terminal 6 and a second cellular mobile telephone terminal 8. In other embodiments, the network 2 may be connected to the public service telephone network (PSTN) and the second terminal 8 may be a telephone terminal or a computer terminal. The first mobile cellular telephone terminal 6 is used by a first user 12 and the second terminal 8 is used by a second user 14.

- Fig. 2 illustrates the first mobile cellular telephone terminal 6 in more detail. It comprises: a radio cellular transceiver 20; a memory 22; a user interface 24 and a control means 30.
- The user interface 24 includes a display 25, a user selection device 26 such a keypad or joystick, an audio output device 27 and an audio input device 28.

The control means 30 is provided, in this example, by a suitably programmed processor. The processor 30 is connected to provide information to and receive information from the radio cellular transceiver 20. This information includes speech and, may, in some embodiments, include data. The processor 30 is connected to read to and to write from the memory 22. The processor 30 is connected to provide display control signals to the display 25 and receive control signals from the selection device 26. During a telephone call, it also provides speech information received from the radio cellular transceiver 20 to the audio output device 28 and provides speech information received from the audio input device 27 to the radio cellular transceiver 20.

5

10

15

20

30

The radio cellular transceiver 20 communicates wirelessly with the infrastructure 4 of the mobile cellular radio telecommunications network 2. This communication enables the terminal 6 to participate in a telephone call with the second terminal 8. The radio cellular transceiver 20 may additionally enable the first terminal 6 to communicate data to the second terminal 8. This may, for example, be as a multimedia messaging service (MMS) message, a short messaging service (SMS) message or as an email message. In other alternative embodiments, the first terminal may comprise an additional transceiver (not shown) for communicating with the second terminal. Such a transceiver is preferably a short-range wireless transceiver such as an infrared (IR) transceiver of a low power radio frequency transceiver such as a Bluetooth (trademark) transceiver.

Fig 3 illustrates the process by which data is sent by the first terminal 6 to the second terminal 8 while it is participating in a telephone call with the second terminal 8. The first user 12 and second user 14 are respective first and second parties to the telephone call. The process occurs within the first terminal 6 and is controlled by the processor 30.

In this example, the call is initiated by the first terminal 6 at step 100. As a consequence of the telephone call the processor 30, at step 102,

automatically stores identifier data identifying the destination of the telephone call in the memory 22. In this case, the destination is the second terminal 8 or its user 14. If the telephone call is a circuit switched telephone call, the identifier data is the telephone number of the second party 14 and the memory 22 is a memory for storing dialled telephone numbers.

If during the telephone call the first party 12 wishes to send a data message to the other party 14, she makes a selection at step 104. The processor 30 responds to this selection at step 106 by controlling the display to provide a number of alternative user selectable options. The provided options depend upon the application from which the selection at step 104 is made. However, at least one option is "send to caller", the selection of which at step 108 enables a data message to be sent without the user input of a destination address.

The application is preferably context aware in the sense that it is aware that a telephone call is ongoing and the provided options are temporarily adapted to include "send to caller" as an additional option while the telephone call is ongoing. This may be achieved by setting a flag in the memory 22 to indicate whether a call is on-going or not. The processor 30 responds to the selection at step 106 by reading the flag from the memory 22. If the flag indicates that a telephone call is not on-going the options provided at step 106 include the option "send" but not the "send to caller" option. Selection of the "send" option enables a data message to be sent after the user has input a destination address. If the flag indicates that a telephone call is on-going the options provided at step 106 include the option "send to caller" in addition to the option "send", thus augmenting the provided options.

One type of application is a data handling application such as a calendar application that stores appointments. The selection at step 104 enables a user to send details of an appointment as a data message. The selection at step 108 enables a user to send details of an appointment as a data message to

the other party participating in an on-going telephone call without inputting the destination address. Another type of data handling message is a contacts application that stores contact details as a series of entries. Each entry may include a postal addresses, telephone numbers and email addresses. The selection at step 104 enables a user to send details from an entry as a data message. The selection at step 108 enables a user to send details from an entry as a data message to the other party participating in an on-going telephone call without inputting the destination address.

5

20

25

Another type of application is a data creation application such as a text entry application, a video camera application or a digital camera application. The selection at step 104 enables a user to send respectively text, a video clip or an image as a data message. The selection at step 108 enables a user to send respectively text, a video clip or an image as a data message to the other party participating in an on-going telephone call without inputting the destination address.

When the "send to caller" option is selected at step 108, the processor 30 at step 110 automatically determines a destination address for the data message using the identifier data stored at step 102. The processor 30 automatically interrogates a database using the telephone number stored at step 102 to obtain the destination address. The database associates different telephone numbers with the data delivery addresses of different persons. Each different identifier data is associated with the data delivery addresses of one person such as their email address, their telephone number, or their Bluetooth device address. The database may be the same database used by the Contacts application.

Then having determined the data delivery addresses, the processor 30 at step 112 controls the display to present for user selection one or more delivery mechanisms related to the determined delivery addresses.

If the determined delivery addresses includes a mobile telephone number, the delivery mechanisms may include: Short Messaging Service (SMS) which is suitable for alphanumeric text or Multimedia Messaging Service (MMS) which is suitable for still images.

5

10

The delivery mechanisms presented may be related to the application from which the selection has been made. Thus SMS is only presented if the selection is from an application that is text-based such as a Calendar, Contacts or text messaging. Thus MMS is only presented if the selection is from an application that is image-based such a digital camera application.

If the determined delivery addresses includes an email address the delivery mechanisms may include email, which is suitable for having text or mark-up language as its body and files as attachments, such as image or video files.

15

If the determined delivery addresses includes a Bluetooth Device address the delivery mechanism will include packet data.

20

25

At step 114 the user selects one of the presented delivery mechanisms.

At step 116, the processor controls the sending of the data message by the selected delivery mechanism using the destination address determined at step 110. The data message is sent via a new channel that runs in parallel with the voice channel used for the telephone call. If the data message is sent using the radio cellular transceiver it may be sent on a separate transport layer to the voice call.

If there is only a single data delivery mechanism available steps 112 and 114 may be automated.

30

Fig 4 also illustrates the process by which data is sent by the first terminal to the second terminal while it is participating in a telephone call with the second terminal. The steps 106 to 11 are the same the steps 100' and 102' are different to the steps 100 and 102 in Fig. 3. In this example, the call is initiated by the first terminal at step 100'. As a consequence of the telephone call, at step 102', the processor 30 automatically stores identifier data identifying the origin of the telephone call in the memory. In this case, the destination is the second terminal or its user. If the telephone call is a circuit switched telephone call, the identifier data is the telephone number of the second party received via the radio cellular transceiver using call line identification (CLI) or its equivalent. However, when the "send to caller" option is selected at step 108, the processor 30 at step 110 automatically determines a destination address for a data message using the identifier data stored at step 102' not step 102.

I/we claim:

CLAIMS

5

- 1. A method of sending data from a first party participating in a telephone call to a second party participating in the telephone call, comprising, in the terminal of the first party,
 - storing, as a consequence of the telephone call, identifier data that identifies the second party;
 - using the stored identifier data to determine automatically a destination address for a data message; and
- sending, during the telephone call, the data message with the automatically determined destination address.
 - 2. A method as claimed in claim1, wherein the telephone call is initiated at the terminal of the first party and the step of storing the identifier data comprises storing the destination of the telephone call.
 - 3. A method as claimed in claim 2, wherein the telephone call is a circuit switched telephone call and the identifier data is the telephone number of the second party.

20

- 4. A method as claimed in claim 1, wherein the telephone call is terminated at the terminal of the first party and the step of storing identifier data comprises storing the origin of the telephone call.
- 5. A method as claimed in claim 4, wherein the telephone call is a circuit switched telephone call and the identifier data is the telephone number of the second party.
- 6. A method as claimed in claim 4, wherein the telephone number of the second party is provided by call line identification (CLI) or equivalent.

7. A method as claimed in any preceding claim wherein the step of using the stored identifier data to determine automatically a destination address for a data message comprises automatically interrogating a database using the identifier data to obtain the destination address.

5

20

25

30

- 8. A method as claimed in claim 7 wherein the database associates the identifier data with contact addresses of the second party.
- A method as claimed in any preceding claim wherein the destination
 address is any one of: an email address, a telephone number, a Bluetooth device address.
- 10. A method as claimed in any preceding claim further comprising:
 providing, only during the telephone call, a user selectable option to transfer
 data to the other party participating in the telephone call without user specification of a destination address.
 - 11. A method as claimed in claim 10, wherein the user selection of the temporarily provided transfer option enables, in the terminal of the first user, the step of using the stored identifier data to determine automatically a destination address for a data message.
 - 12. A mobile cellular telephone terminal comprising:
 - a radio cellular transceiver for enabling participation in a telephone call to a second terminal;
 - a memory; and

control means for storing in the memory, as a consequence of the telephone call, identifier data identifying the second terminal or its user, for determining automatically a destination address for a data message using the stored identifier data and for controlling the radio cellular transceiver to send the data message with the automatically determined destination address during the telephone call.

- 13. A mobile telephone terminal as claimed in claim 12, wherein the stored identifier data is a dialled telephone number.
- 5 14. A mobile telephone terminal as claimed in claim 12, wherein the stored identifier data is a telephone number received via the radio cellular transceiver.
- 15. A mobile telephone terminal as claimed in claim 12, 13 or 14, further 10 comprising a database, wherein the control means is operable to interrogate the database using the identifier data to obtain the destination address.
 - 16. A mobile telephone terminal as claimed in claim 15, wherein the database associates each of a plurality of different the identifier data with respective different contact addresses.
 - 17. A mobile telephone terminal as claimed in any one of claims 12 to 16, wherein the destination address is any one of: an email address, a telephone number, a Bluetooth device address.

18. A mobile telephone terminal as claimed in any one of claims 12 to 17, further comprising a user interface for providing a user selectable option to transfer data to another party participating in the telephone call without user

specification of a destination address.

19. A mobile telephone terminal as claimed in claim 18, wherein the user selectable option is provided only during the telephone call .

20. A method for sending data from a first party participating in a telephone 30 call to a second party participating in the telephone call, comprising, in the terminal of the first party:

25

20

providing, while the telephone call is on-going, a user selectable option to transfer data to another party participating in the telephone call without user specification of a destination address.

5 21. A method as claimed in claim 20, wherein selecting the provided option enables user selection of one of a plurality of delivery mechanisms.

10

- 22. A method as claimed in claim 20, wherein selecting the provided option enables automatic selection of a delivery mechanism.
- 23. A method as claimed in claim 20, wherein the step of providing, while the telephone call is on-going, a user selectable option to transfer data to another party participating in the telephone call without user specification of a destination address provides more that one user selectable option to transfer data to another party participating in the telephone call without user specification of a destination address, wherein each option enables a different delivery mechanism.
- 24. A method as claimed in any one of claims 20 to 23, further comprising automatically storing, as a consequence of the telephone call, data that identifies the second party, wherein selecting a provided option enables using the stored data to determine automatically a destination address for a data message.
- 25. A method as claimed in any one of claims 20 to 23, further comprising sending the data message with the determined destination address.
 - 26. A method as claimed in claim 24 or 25, wherein the destination address is any one of: email address, telephone number, Bluetooth device address
- 30 27. A method as claimed in any one of claims 20 to 26, wherein the step of providing, while the telephone call is on-going, a user selectable option to transfer data to another party participating in the telephone call without user

specification of a destination address temporarily augments automatically a user selectable data transfer option for transferring data to a user determined destination address.

- 5 **28**. A mobile cellular telephone terminal comprising:
 - a radio cellular transceiver for enabling participation in a telephone call to a second terminal;
 - a user interface; and


- control means for providing, temporarily while the telephone call is on-going, in the user interface a user selectable option to transfer data to another party participating in the telephone call without user specification of a destination address.
- 29. A mobile cellular telephone terminal as claimed in claim 28, wherein the control means responds to user selection of the provided option to provide a plurality of user selectable delivery mechanisms.
- 30. A mobile cellular telephone terminal as claimed in claim 28, wherein the control means responds to user selection of the provided option to
 20 automatically select a delivery mechanism.
 - 30. A mobile cellular telephone terminal as claimed in claim 28, wherein the control means automatically stores, as a consequence of the telephone call, data that identifies the second party and is responsive to the user selection of provided option to automatically determine, using the stored data, a destination address for a data message.
- 31. A mobile cellular telephone terminal as claimed in claim 30, wherein control means controls the radio transceiver to send a data message with the determined destination address.

32. A mobile cellular telephone terminal as claimed in claim 30 or 31, wherein the destination address is any one of: an email address, a telephone number, and a Bluetooth device address.

ABSTRACT

A method of sending data from a first party participating in a telephone call to a second party participating in the telephone call, comprising, in the terminal of the first party, storing, as a consequence of the telephone call, identifier data that identifies the second party; using the stored identifier data to determine automatically a destination address for a data message; and sending, during the telephone call, the data message with the automatically determined destination address. A method for sending data from a first party participating in a telephone call to a second party participating in the telephone call, comprising, in the terminal of the first party: providing, while the telephone call is on-going, a user selectable option to transfer data to another party participating in the telephone call without user specification of a destination address.

Fig. 3






Fig. 2

EXHIBIT E

